

Hybrid Dolly - versatile load carrier





Designed for following uses and industries:



Key benefits

- Ready to sell unit
- Easy branding and marking
- Suitable for automated order-picking
- Stackable for space savings
- Silent with optional PIEK certified wheels
- Suitable for automated handling

Strong and versatile, ½ pallet Hybrid Dolly is constructed with plastic deck and metal reinforcements. It is also equipped with anti-slip strips to prevent the packages from gliding. It can support different sizes and types of plastic crates and trays and is ideal for storing, transporting and displaying bulk products. Hybrid Dolly can also be supplied with PIEK certified rubber wheels.

As with all K. Hartwall dollies, Hybrid Dolly offers one-touch logistics and is ready for display locking. Hybrid Dolly is also suitable for multiple uses and various transportation systems for a long life-span and low total cost of ownership.

Technical specifications	
DOS1527	with compound wheels
DOS1582	with rubber wheels (PIEK certified)
External dimensions	800 x 600 x 198 mm
Internal dimensions	780 x 580 x 7 mm
Unit tare weight DOS1527	9,5 kg
Unit tare weight DOS1582	10,2 kg
Safe working load	500 kg
Stacked units / 45' trailer	924
Stacking height	164,5 mm
Deck	HDPE
Castor size	100 mm
Castor type	2 fixed, 2 swivel
Handling space between wheels	425/589 mm

Noise Level for DOS1582

60 dB(A)

For full list of standard equipment and optional accessories visit: khartwall.com/products